



Printing: CAT 6A U/UTP 500 MHz ISO/IEC 11801 &  
ANSI/TIA -C2 #315# mm/yyyy  
Wentronic GmbH | Pöhlmannstraße 12 | 38112 Braunschweig Germany



**PIN OUT**

P1		P2	
1		1	WHITE/ORANGE
2		2	ORANGE
3		3	WHITE/GREEN
6		6	GREEN
4		4	BLUE
5		5	WHITE/BLUE
7		7	WHITE/BROWN
8		8	BROWN

Spezifikation / Specification	CAT 6A
Kabeltyp / Cable type	Rundkabel / round cable
Innenleiter, Material / Inner conductor material	CCA (kupferkaschiertes Aluminium) / CCA (copper-clad aluminium)
Innenleiter, Aderdurchmesser / Inner conductor, core diameter	(7/0.19 ± 0.005 mm)
AWG	25/7 (stranded)
Schirmungsklasse / Shielding class	U/UTP
Durchmesser Kabelmantel (ca.) / Cable sheath diameter (approx.)	∅ 5.9 ± 0.2 mm, PE CROSS+PVC
Knickschutz / Kink protection	beidseitig / both sides
Anschluss, Typ / Connection, type	RJ45-Stecker 90° (8P8C) / RJ45 male 90° (8P8C)
Anschluss, Schirmung / Connection, shielding	nein / no
Anschluss 2, Typ / Connection 2, type	RJ45-Stecker (8P8C) / RJ45 male (8P8C)
Rastnasenschutz / Latch protection	einseitig / unilaterally
max. Bandbreite / max. bandwidth	500 MHz



**CAT 6A Patchkabel 1x 90° gewinkelt, U/UTP**

- ungeschirmtes LAN/Netzwerkkabel zum Anschluss Ihrer Netzwerkkomponenten mit 2x RJ45 Steckern
- RJ45-Stecker gerade an RJ45-Stecker gewinkelt, ideale Lösung bei minimalen Platzverhältnissen
- mit vergoldeten Kontaktflächen (PINs)
- Slimline-Knickschutzülle
- Rastnasenschutz und Längenangabe am geraden Stecker
- geeignet für Power over Ethernet (PoE/PoE+)
- Betriebstemperatur: -20 °C bis 65 °C

**CAT 6A patch cable 1x 90° angled, U/UTP**

- unshielded LAN/network cable to connect network components with 2 x RJ45 connectors
- RJ45 plug straight to RJ45 plug angled, ideal solution with minimal space
- with gold plated PINs
- slimline strain relief
- Latch protection and length indication on straight plug
- adatto per Power over Ethernet (PoE/PoE+)
- Operating temperature: -20 °C up to 65 °C

Farbe / Colour	Art.	Farbe / Colour	Art.	L [m]	T [mm]	Remark
	51527	weiß / white	51534	0.25	± 20	with cable tag
	51528		51535	0.50	± 20	without cable tag
	51529		51536	1.00	± 20	without cable tag
	51530		51537	2.00	± 40	without cable tag
	51531		51538	3.00	± 50	without cable tag
	51532		51539	5.00	± 70	without cable tag
	51533		51540	10.00	± 100	without cable tag

**Änderungen**

Datum	Name	gez.:	Datum	Name
24.01.2025	ir		30.09.2020	sm
		gepr.:	30.09.2020	ac
		Norm:		

Änderungen vorbehalten / Subject to change

Bezeichnung  
**CAT 6A-xxxx U/UTP (1x90°) CCA**  
 x.xx m  
 Zeichnungs-Nr.:  
**51527ff**



Blatt

von